

Colour: White



product properties

| article | system | Roll Length | Roll Width | | Number of Sheets | Sheet Length | Core Inner Diameter | Ply | Colour |
|---------|---|-------------|------------|-------|---------------------|--------------|------------------------|-----|--------|
| 530137 | W1 - Wipers wall/floor/sta ndard system, W2 - Wipers combi roll system, W3 - Wiper pak system | 106.4 m | 32 cm | 25 cm | 280 | 38 cm | 7.13 cm | 1 | White |

description

This strong and absorbent multipurpose cloth works with most solvents. It is designed to protect your hands from heat and metal scraps. The cloth provides a professional cleaning result thanks to the exelCLEAN[™] effect.



Colour: White

shipping data

TORK

consumer unit

| EAN | 7322540057553 |
|--------------|---------------|
| pieces | 1 |
| height | 338 mm |
| width | 264 mm |
| length | 264 mm |
| volume | 23.6 dm3 |
| net weight | 2724 g |
| gross weight | 3042 g |

transport unit

| EAN | 7322540057553 | | |
|----------------|---------------|--|--|
| pieces | 1 | | |
| consumer units | 1 | | |
| material | Carton | | |
| height | 338 mm | | |
| width | 264 mm | | |
| length | 264 mm | | |
| volume | 23.6 dm3 | | |
| net weight | 2.72 kg | | |
| gross weight | 3.04 kg | | |

pallet

| EAN | 7322540748475 | | |
|----------------|---------------|--|--|
| pieces | 36 | | |
| consumer units | 36 | | |
| height | 1175 mm | | |
| width | 1000 mm | | |
| length | 1200 mm | | |
| volume | 0.8 m3 | | |
| net weight | 98.06 kg | | |
| gross weight | 109.51 kg | | |



environmental

Content

Cellulose pulp Polypropylene fibres Polyester fibres Chemicals

Material

Cellulose pulp

Cellulose pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals to remove the lignin between the fibres. The pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities.

There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free).

ECF is based on oxygene, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone. ECF is used in this product.

Polypropylene

Polypropylene fibres is produced from polypropylene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Polyester

Polyester fibre is produced from terephtalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibrelength.

Chemicals

Both functional and process chemicals are used. The functional chemical used

is a wetstrength agent. The wetstrength agent is a polyamide (from polyamidine/epichlorhydrinepolymer) with a very high affinity to the fibre.

The process chemical used is a surfactant.

Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Food Contact

This product fulfils the legislative requirements for Food Contact materials, confirmed by external certification performed by ISEGA. The product is safe for wiping food contact surfaces and may also come occasionally into





Colour: White

contact with foodstuffs for a short period of time.

Disposing / destruction of used product

This product is mainly used for industrial processes and might through use be contaminated with different substances. This will determine how the used product will be handled / disposed of / destructed. The product itself is suitable for incineration. Contact local authorities before destruction.

