

MAXX BRIAL S**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : MAXX BRIAL S

Product code : 118701E

Use of the Substance/Mixture : All Purpose Cleaner

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : General purpose cleaner - Manual process, without PPE
General purpose cleaner. Manual process
General purpose cleaner. Spray and wipe manual process

Recommended restrictions on use : Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com

1.4 Emergency telephone number

Emergency telephone number : +441618841235
+32-(0)3-575-5555 Trans-European

Poison Information Centre telephone number : For medical professionals only: 0344 892 0111

Date of Compilation/Revision : 13.02.2023
Version : 1.2

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

MAXX BRIAL S

The classification of this product is based on toxicological assessment.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

Special labelling of certain mixtures : Safety data sheet available on request.

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Hazardous components

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration : [%]
ethanol	64-17-5 200-578-6 01-2119457610-43	Flammable liquids Category 2; H225 Serious eye damage/eye irritation Category 2; H319 Serious eye damage/eye irritation Category 2 50 - 100 %	>= 5 - < 10
Di(2-Ethylhexyl) Sodium Sulfosuccinate	577-11-7 209-406-4 01-2119491296-29	Skin irritation Category 2; H315 Serious eye damage Category 1; H318	>= 1 - < 2.5

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES

4.1 Description of first aid measures

- In case of eye contact : Rinse with plenty of water.
- In case of skin contact : Rinse with plenty of water.
- If swallowed : Rinse mouth. Get medical attention if symptoms occur.
- If inhaled : Get medical attention if symptoms occur.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : No specific measures identified.

Section: 5. FIREFIGHTING MEASURES

MAXX BRIAL S

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Fire Hazard
Keep away from heat and sources of ignition.
Flash back possible over considerable distance.
Beware of vapours accumulating to form explosive concentrations.
Vapours can accumulate in low areas.
- Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
metal oxides
Sulphur oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : Use personal protective equipment.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

- Advice for non-emergency personnel : Remove all sources of ignition. Refer to protective measures listed in sections 7 and 8.
- Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

- Environmental precautions : No special environmental precautions required.

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

- See Section 1 for emergency contact information.

MAXX BRIAL S

For personal protection see section 8.
See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

- Advice on safe handling : Keep away from fire, sparks and heated surfaces. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
- Hygiene measures : Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep away from heat and sources of ignition. Keep away from oxidizing agents. Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.
- Storage temperature : 0 °C to 40 °C

7.3 Specific end uses

- Specific use(s) : General purpose cleaner - Manual process, without PPE
General purpose cleaner. Manual process
General purpose cleaner. Spray and wipe manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ethanol	64-17-5	TWA	1,000 ppm 1,920 mg/m3	UKCOSSTD

DNEL

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	:	End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 175 mg/m3
	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 2750 mg/m3
	:	End Use: Workers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.132 mg/m3
	:	End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects

MAXX BRIAL S

	<p>Value: 52 mg/m³</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 1650 mg/m³</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term local effects Value: 0.079 mg/m³</p> <p>End Use: Consumers Exposure routes: Oral Potential health effects: Long-term systemic effects Value: 15 mg/m³</p>
oxydipropanol	<p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 238 mg/m³</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 84 mg/cm²</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 70 mg/m³</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 51 mg/cm²</p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 24 ppm</p>

PNEC

Linear(C12-C14)alkanol, ethoxylated, sulfated, sodium salt	<p>: Fresh water Value: 0.24 mg/l</p> <p>Marine water Value: 0.024 mg/l</p> <p>Sewage treatment plant Value: 10000 mg/l</p> <p>Fresh water sediment Value: 0.917 mg/kg</p> <p>Marine sediment</p>
--	---

MAXX BRIAL S

	Value: 0.092 mg/kg Soil Value: 7.5 mg/kg
oxydipropanol	: Fresh water Value: 0.1 mg/l Marine water Value: 0.01 mg/l Fresh water Value: 1 mg/l Intermittent use/release Value: 2 mg/l Fresh water sediment Value: 0.238 mg/kg Marine sediment Value: 0.0238 mg/kg Sewage treatment plant Value: 1000 mg/l Soil Value: 0.0253 mg/kg Oral Value: 313 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands before breaks and immediately after handling the product.

Eye/face protection (EN 166) : No special protective equipment required.

Hand protection (EN 374) : No special protective equipment required.

Skin and body protection (EN 14605) : No special protective equipment required.

Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by

MAXX BRIAL S

technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: clear, light blue
Odour	: pleasant
pH	: 6.3 - 7.3
Flash point	: 43 °C closed cup, Does not sustain combustion.
Odour Threshold	: Not applicable and/or not determined for the mixture
Melting point/freezing point	: Not applicable and/or not determined for the mixture
Initial boiling point and boiling range	: > 100 °C
Evaporation rate	: Not applicable and/or not determined for the mixture
Flammability (solid, gas)	: Not applicable and/or not determined for the mixture
Upper explosion limit	: Not applicable and/or not determined for the mixture
Lower explosion limit	: Not applicable and/or not determined for the mixture
Vapour pressure	: Not applicable and/or not determined for the mixture
Relative vapour density	: Not applicable and/or not determined for the mixture
Relative density	: 0.986 - 0.992
Water solubility	: Not applicable and/or not determined for the mixture
Solubility in other solvents	: Not applicable and/or not determined for the mixture
Partition coefficient: n-octanol/water	: Not applicable and/or not determined for the mixture
Auto-ignition temperature	: Not applicable and/or not determined for the mixture
Thermal decomposition	: Not applicable and/or not determined for the mixture
Viscosity, kinematic	: Not applicable and/or not determined for the mixture
Explosive properties	: Not applicable and/or not determined for the mixture
Oxidizing properties	: The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

MAXX BRIAL S

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:

Carbon oxides
Sulphur oxides
metal oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : There is no data available for this product.

Acute inhalation toxicity : There is no data available for this product.

Acute dermal toxicity : There is no data available for this product.

Skin corrosion/irritation : Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization : There is no data available for this product.

Carcinogenicity : There is no data available for this product.

Reproductive effects : There is no data available for this product.

Germ cell mutagenicity : There is no data available for this product.

Teratogenicity : There is no data available for this product.

STOT - single exposure : There is no data available for this product.

STOT - repeated exposure : There is no data available for this product.

MAXX BRIAL S

Aspiration toxicity : There is no data available for this product.

Components

Acute oral toxicity : ethanol LD50 rat: 10,470 mg/kg
Di(2-Ethylhexyl) Sodium Sulfosuccinate LD50 rat: 3,000 mg/kg

Components

Acute inhalation toxicity : ethanol 4 h LC50 rat: 117 mg/l
Test atmosphere: vapour

Components

Acute dermal toxicity : ethanol LD50 rabbit: 15,800 mg/kg
Di(2-Ethylhexyl) Sodium Sulfosuccinate LD50 rabbit: > 10,000 mg/kg

Potential Health Effects

Eyes : Health injuries are not known or expected under normal use.

Skin : Health injuries are not known or expected under normal use.

Ingestion : Health injuries are not known or expected under normal use.

Inhalation : Health injuries are not known or expected under normal use.

Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

Eye contact : No symptoms known or expected.

Skin contact : No symptoms known or expected.

Ingestion : No symptoms known or expected.

Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Toxicity

Environmental Effects : This product has no known ecotoxicological effects.

Product

Toxicity to fish : no data available

Toxicity to daphnia and other aquatic invertebrates : no data available

Toxicity to algae : no data available

Components

Toxicity to fish : ethanol 96 h LC50 Pimephales promelas (fathead minnow): > 100 mg/l

MAXX BRIAL S

Di(2-Ethylhexyl) Sodium Sulfosuccinate 96 h LC50 Danio rerio (zebra fish): 49 mg/l

Components

Toxicity to daphnia and other aquatic invertebrates : ethanol 48 h EC50 Aquatic Invertebrate: 857 mg/l

Di(2-Ethylhexyl) Sodium Sulfosuccinate 48 h EC50 Daphnia magna (Water flea): 6.6 mg/l

Components

Toxicity to algae : Di(2-Ethylhexyl) Sodium Sulfosuccinate 72 h EC50 Desmodesmus subspicatus (green algae): 82.5 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : ethanol Result: Readily biodegradable.

Di(2-Ethylhexyl) Sodium Sulfosuccinate Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

Product : Diluted product can be flushed to sanitary sewer if regulations

MAXX BRIAL S

permit.

- Contaminated packaging : Dispose of in accordance with local, state, and federal regulations.
- Guidance for Waste Code selection : Organic wastes containing not dangerous substances with concentration $\geq 0.1\%$. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods

Air transport (IATA)

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods

Sea transport (IMDG/IMO)

- 14.1 UN number : Not dangerous goods
- 14.2 UN proper shipping name : Not dangerous goods
- 14.3 Transport hazard class(es) : Not dangerous goods
- 14.4 Packing group : Not dangerous goods
- 14.5 Environmental hazards : Not dangerous goods
- 14.6 Special precautions for user : Not dangerous goods
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC : Not dangerous goods

MAXX BRIAL S

Code

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents : less than 5 %: Anionic surfactants
 Regulation EC 648/2004 Contains: Perfumes

Seveso III: Directive : Not applicable.
 2012/18/EU of the European
 Parliament and of the Council
 on the control of major-
 accident hazards involving
 dangerous substances.

Candidate List of Substances : Not applicable.
 of Very High Concern for
 Authorisation

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply)
 Regulations.
 The Control of Substances Hazardous to Health Regulations.
 Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Not a hazardous substance or mixture.	Calculation method

Full text of H-Statements

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System;

MAXX BRIAL S

GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: General purpose cleaner. Spray and wipe manual process

Life Cycle Stage : Widespread use by professional workers
Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems
Daily amount per site : 7.5 kg
Type of Sewage Treatment Plant : Municipal sewage treatment plant

MAXX BRIAL S

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing
Exposure duration : 480 min
Operational conditions and risk management measures : Indoor
Local Exhaust Ventilation is not required
General ventilation Ventilation rate per hour 1
Skin Protection : see section 8
Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
Exposure duration : 60 min
Operational conditions and risk management measures : Indoor
Local Exhaust Ventilation is not required
General ventilation Ventilation rate per hour 1
Skin Protection : see section 8
Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC11** Non industrial spraying
Exposure duration : 60 min
Operational conditions and risk management measures : Indoor
Local Exhaust Ventilation is not required
General ventilation Ventilation rate per hour 1
Skin Protection : see section 8
Respiratory Protection : see section 8

Exposure Scenario: General purpose cleaner. Manual process

Life Cycle Stage : Widespread use by professional workers
Product category : **PC35** Washing and cleaning products (including solvent based

MAXX BRIAL S

products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems
Daily amount per site : 7.5 kg
Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing
Exposure duration : 480 min
Operational conditions and risk management measures : Indoor
Local Exhaust Ventilation is not required
General ventilation Ventilation rate per hour 1
Skin Protection : see section 8
Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities
Exposure duration : 60 min
Operational conditions and risk management measures : Indoor
Local Exhaust Ventilation is not required
General ventilation Ventilation rate per hour 1
Skin Protection : see section 8
Respiratory Protection : see section 8

Exposure Scenario: General purpose cleaner - Manual process, without PPE

Life Cycle Stage : Widespread use by professional workers
Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release : **ERC8a** Wide dispersive indoor use of processing aids in open

MAXX BRIAL S

category : systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation : Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation : Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Exposure Scenario: General purpose cleaner - Manual process, without PPE

Life Cycle Stage : Widespread use by professional workers

Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems

Daily amount per site : 7.5 kg

Type of Sewage Treatment Plant : Municipal sewage treatment plant

MAXX BRIAL S

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : see section 8

Respiratory Protection : see section 8